

Modular Force10 Operating System (FTOS) software delivers inherent stability

24-port SFP fixed configuration 1-RU switch with up to four 10 GbE uplinks

Scalable stacking technology supports 192 fiber 100M or GbE ports in up to eight S25Ps

### S-Series S25P High Performance GbE/10 GbE Access Switch

The Force10 S25P is a compact form factor switch that delivers high Gigabit Ethernet fiber density at the network edge, enabling cost-effective scalability while eliminating bandwidth bottlenecks at key aggregation points.

#### Key Applications

Coupled with the E-Series and C-Series, which deliver unmatched resiliency and performance, the S25P enables IT managers to deploy a reliable end-to-end 10 GbE solution that spans from core to network edge.

- Small form factor intra-POP Layer 2 interconnects
- 10 GbE LAN PHY or DWDM XFP media modules for cost-effective metro or inter-POP transport
- Flexible customer aggregation and distribution switch supporting 10/100/1000Base-T copper and 100/1000Mbps fiber
- Line-rate GbE and 10 GbE rack switches for the most demanding data center, storage or compute facility

#### Key Features

The S25P is a reliable and scalable fixed configuration modular media switch for high performance Ethernet environments.

- 24 SFP ports in a 1-RU form factor with two modular slots
  - 20 ports 100Base-FX, 10/100/1000Base-T, or 1000Base-X with SFP media modules
  - 4 ports 10/100/1000Base-T shared with SFP ports
- Optional modules
  - 2-port 10 GbE LAN PHY (pluggable XFP modules)
  - 2-port 10 GbE (CX4)
  - 2-port 12 Gbps stacking
  - 1-port 24 Gbps stacking
- Modular FTOS with advanced monitoring and serviceability functions
- VirtualView real-time network and application traffic monitoring for virtualized data centers
- Supports jumbo frames of up to 9,252 bytes; ideal for high-end server connectivity and network attached file servers
- Full complement of standards-based Layer 2, IPv4 and IPv6 features for unicast and multicast applications
- Switching fabric capacity of 144 Gbps and forwarding capacity of more than 95 Mpps
- Stack up to eight S25N, S25P, S25V, S50N or S50V switches to deliver a scalable and flexible high capacity solution



# Specifications: S-Series S25P Fiber Switch

## Ordering Information

ORDER NUMBER	DESCRIPTION
S25-01-GE-24P-2	24-port 100Base-FX/GbE SFP chassis with four 10/100/1000Base-T ports, two modular slots and two AC power supplies, FTOS software
S25-01-GE-24P-DC-2	24-port 100Base-FX/GbE SFP chassis with four 10/100/1000Base-T ports, two modular slots and two DC power supplies, FTOS software
S50-01-10GE-2P	2-port 10 GbE XFP module
S50-01-10GE-2C	2-port 10 GbE CX4 module
S50-01-12G-2S	2-port 12 Gbps stacking module
S50-01-24G-1S	1-port 24 Gbps stacking module
S50-01-SSC-12G	60 cm stacking cable for S50-01-12G-2S
S50-01-LSC-12G	4 m stacking cable for S50-01-12G-2S
S50-01-SSC-24G	60 cm stacking cable for S50-01-24G-1S
S50-01-LSC-24G	4 m stacking cable for S50-01-24G-1S
SW-SB-LATEST	Layer 3 FTOS software upgrade

## Physical

24 line-rate ports supporting GbE or 100Base-FX SFPs  
4-ports 10/100/1000Base-T (shared with SFP ports)  
1 RJ45 console/management port with RS232 signaling

### Optional modules:

- 2 line-rate ports 10 Gigabit Ethernet XFP
- 2 line-rate ports 10 Gigabit Ethernet CX4
- 2 line-rate ports 12 Gigabit Stacking
- 1 line-rate port 24 Gigabit Stacking

Size: 1 RU, 1.7 h x 17.32 w x 16.73" d (4.3 h x 44 w x 42.5 cm d)  
Weight: 14.43 lbs (6.56 kg)  
ISO 7779 A-weighted sound pressure level: 45.1 dBA at 73.4°F (23°C)  
Power supply:

100–240 VAC 50/60 Hz, –44 to –60 VDC

Max. thermal output:

S25P (AC): 305 BTU/h, S25P (DC): 262 BTU/h

Max. current draw per system:

2 A at 100/120 VAC, 1 A at 200/240 VAC, 3.6 A at –48 VDC

Max. power consumption:

S25P (AC): 90 W, S25P (DC): 77 W

Max. operating specifications:

Operating temperature: 32° to 122°F (0° to 50°C)

Operating humidity: 10 to 85% (RH), non-condensing

Max. non-operating specifications:

Storage temperature: –40° to 158°F (–40 to 70°C)

Storage humidity: 5 to 95% (RH), non-condensing

Reliability:

S25P (AC): MTBF 164,358 hours, S25P (DC): MTBF 164,358 hours

## Redundancy

Ring stacking topology with dynamic master election

Dual modular slots with up to four 10 GbE ports

Link aggregation across stack members

Power redundancy

## Performance

MAC addresses: 16K

IPv4 routes: 4K

IPv6 routes: 2,500

Switching fabric capacity: 144 Gbps

User traffic capacity: 128 Gbps (95 Mpps)

Link aggregation: 8 links per group, 128 groups per stack

Stacking capacity: 96 Gbps per stack member

Queues per port: 4 queues

VLANs: 1024 VLANs with 4096 tag value support

Line-rate Layer 2 switching: all protocols, including IPv4 and IPv6

Line-rate Layer 3 routing: IPv4 and IPv6

LAG load balancing: based on Layer 2, IPv4 or IPv6 headers

Switching latency: <5 µs for 64 byte frames

## IEEE Compliance

802.1AB LLDP

802.1D Bridging, STP

802.1p L2 Prioritization

802.1Q VLAN Tagging, Double VLAN Tagging, GVRP

802.1s MSTP  
802.1w RSTP  
802.1X Network Access Control  
802.3ab Gigabit Ethernet (1000BASE-T)  
802.3ac Frame Extensions for VLAN Tagging  
802.3ad Link Aggregation with LACP  
802.3ae 10 Gigabit Ethernet (10GBASE-X)  
802.3ak 10 Gigabit Ethernet (10GBASE-CX4)  
802.3i Ethernet (10BASE-T)  
802.3u Fast Ethernet (100BASE-FX, 100BASE-TX)  
802.3x Flow Control  
802.3z Gigabit Ethernet (1000BASE-X)  
ANSI/TIA-1057 LLDP-MED  
Force10 PVST+  
MTU 9,252 bytes

## RFC and I-D Compliance

### General Internet Protocols

768	UDP	1321	MD5
793	TCP	1350	TFTP
854	Telnet	2474	Differentiated Services
959	FTP	3164	Syslog

### General IPv4 Protocols

791	IPv4	1812	Routers
792	ICMP	1858	IP Fragment Filtering
826	ARP	2131	DHCP (relay)
1027	Proxy ARP	2338	VRPP
1035	DNS (client)	3021	31-bit Prefixes
1042	Ethernet Transmission	3046	DHCP Option 82
1191	Path MTU Discovery	3069	Private VLAN
1305	NTPv3	3128	Tiny Fragment Attack Protection
1519	CIDR		
1542	BOOTP (relay)		

### General IPv6 Protocols

1981	Path MTU Discovery (partial)	2463	ICMPv6
		2464	Ethernet Transmission
2460	IPv6	2675	Jumbograms
2461	Neighbor Discovery (partial)	3587	Global Unicast Address Format
2462	Stateless Address Autoconfiguration (partial)	4291	Addressing

## RIP

1058	RIPv1	2453	RIPv2
------	-------	------	-------

## OSPF

2154	MD5	3623	Graceful Restart
1587	NSSA	4222	Prioritization and Congestion Avoidance
2328	OSPFv2		
2370	Opaque LSA		

## BGP

1997	Communities	2858	Multiprotocol Extensions
2385	MD5	2918	Route Refresh
2439	Route Flap Damping	3065	Confederations
2796	Route Reflection	4360	Extended Communities
2842	Capabilities	4893	4-byte ASN
draft-ietf-idr-bgp4-20	BGPv4		
draft-ietf-idr-restart-06	Graceful Restart		
draft-michaelson-4byte-as-representation-05	4-byte ASN Representation (partial)		

## Multicast

1112	IGMPv1		
2236	IGMPv2		
3376	IGMPv3		
3569	SSM for IPv4		
4541	IGMPv1/v2 Snooping		
draft-ietf-pim-sm-v2-new-05	PIM-SM		

## Network Management

1155	SMLv1		
1156	Internet MIB		
1157	SNMPv1		
1212	Concise MIB Definitions		
1215	SNMP Traps		
1493	Bridges MIB		
1850	OSPFv2 MIB		
1901	Community-based SNMPv2		
2011	IP MIB		
2012	TCP MIB		

2013	UDP MIB		
2024	DLsw MIB		
2096	IP Forwarding Table MIB		
2570	SNMPv3		
2571	Management Frameworks		
2572	Message Processing and Dispatching		
2574	SNMPv3 USM		
2575	SNMPv3 VACM		
2576	Coexistence Between SNMPv1/v2/v3		
2578	SMLv2		
2579	Textual Conventions for SMLv2		
2580	Conformance Statements for SMLv2		
2618	RADIUS Authentication MIB		
2665	Ethernet-like Interfaces MIB		
2674	Extended Bridge MIB		
2787	VRPP MIB		
2819	RMON MIB (groups 1, 2, 3, 9)		
2863	Interfaces MIB		
2865	RADIUS		
3273	RMON High Capacity MIB		
3416	SNMPv2		
3418	SNMP MIB		
3434	RMON High Capacity Alarm MIB		
3580	802.1X with RADIUS		
5060	PIM MIB		
ANSI/TIA-1057	LLDP-MED MIB		
draft-grant-tacacs-02	TACACS+		
draft-ietf-idr-bgp4-mib-06	BGP MIBv1		
IEEE 802.1AB	LLDP MIB		
IEEE 802.1AB	LLDP DOT1 MIB		
IEEE 802.1AB	LLDP DOT3 MIB		
ruzin-mstp-mib-02	MSTP MIB (traps)		
sFlow.org	sFlowv5		
sFlow.org	sFlowv5 MIB (version 1.3)		
FORCE10-BGP4-V2-MIB	Force10 BGP MIB (draft-ietf-idr-bgp4-mibv2-05)		

FORCE10-IF-EXTENSION-MIB	
FORCE10-LINKAGG-MIB	
FORCE10-COPY-CONFIG-MIB	
FORCE10-MON-MIB	
FORCE10-PRODUCTS-MIB	
FORCE10-SS-CHASSIS-MIB	
FORCE10-SMI	
FORCE10-SYSTEM-COMPONENT-MIB	
FORCE10-TC-MIB	
FORCE10-TRAP-ALARM-MIB	

## Regulatory Compliance

### Safety

UL/CSA 60950-1, 1st Edition  
EN 60950-1, 1st Edition  
IEC 60950-1, 1st Edition Including all National Deviations and Group Differences  
EN 60825-1 Safety of Laser Products Part 1: Equipment Classification Requirements and User's Guide  
EN 60825-2 Safety of Laser Products Part 2: Safety of Optical Fibre Communication Systems  
FDA Regulation 21 CFR 1040.10 and 1040.11

### Emissions

Australia/New Zealand: AS/NZS CISPR 22: 2006, Class A  
Canada: ICES-003, Issue-4, Class A  
Europe: EN 55022: 2006 (CISPR 22: 2006), Class A  
Japan: VCCI V3/2007.04 Class A  
USA: FCC CFR 47 Part 15, Subpart B, Class A

### Immunity

EN 300 386 V1.3.3: 2005 EMC for Network Equipment  
EN 55024: 1998 + A1: 2001 + A2: 2003  
EN 61000-3-2: Harmonic Current Emissions  
EN 61000-3-3: Voltage Fluctuations and Flicker  
EN 61000-4-2: ESD  
EN 61000-4-3: Radiated Immunity  
EN 61000-4-4: EFT  
EN 61000-4-5: Surge  
EN 61000-4-6: Low Frequency Conducted Immunity

### RoHS

All S-Series components are EU RoHS compliant.

The features and specifications are for FTOS. For SFTOS features and specifications, please refer to the SFTOS data sheet.



## Force10 Networks, Inc.

350 Holger Way  
San Jose, CA 95134 USA  
www.force10networks.com

408-571-3500 PHONE  
408-571-3550 FACSIMILE

© 2009 Force10 Networks, Inc. All rights reserved. Force10 Networks and E-Series are registered trademarks, and Force10, the Force10 logo, Force10 Reliable Networking, C-Series, EtherScale, FlexMedia, FTMS, FTOS, Hot Lock, PowerSmart, P-Series, Reliable Business Networking, SFTOS, S-Series, StarSupport, TeraScale, VirtualControl, VirtualScale, and VirtualView are trademarks of Force10 Networks, Inc. All other company names are trademarks of their respective holders. Information in this document is subject to change without notice. Certain features may not yet be generally available. Force10 Networks, Inc. assumes no responsibility for any errors that may appear in this document.

SSDS04

109 v4.0